

Aero Range - Wi-Fi 7 Ceiling AP

SIL WCAP-7X

All New Robust Performance, Wireless Ceiling Access Point



SIL WCAP-7X
10Gbps 802.11AX Dual
Band Wireless Ceiling AP

OVERVIEW

The SIL WCAP-7X is a compact ceiling access point that offers robust performance in an elegant design.

As part of the new Intelligent Wi-Fi 7 "Aero" range by SilverNet, the cloud-managed WCAP-7X is designed to build high performance enterprise Wi-Fi networks and make enterprise management simple.

Offering superior indoor Wi-Fi range, it can provide integrated Power Over Ethernet via 48V PoE or 12V DC. This means it is perfect for a number of uses, particularly commercial and hospitality applications. From providing hotspot functionality, to supporting various hotspot authentication methods such as vouchers, local accounts or, for example, Facebook, it provides strong support across shopping centres, schools, hotels and more.

With options to manage the AP locally or via the cloud, the flexibility of this equipment allows you to offer a full, end-to-end managed Wi-Fi service to meet your client's needs. It is also efficient when used as a standalone AP.

Keep things running smoothly for both you and your customer. You'll stay informed about your customer's Wi-Fi client signal health and internet quality, putting an end to common, unnecessary support calls. Time consuming tasks like RF troubleshooting and bulk software upgrades are a breeze, and installation is a simple, speedy job.

The 5GHz priority feature improves wireless network performance, and with 1 year extended warranty you won't have to worry about your customer's Wi-Fi needs.

Features

- WIFI 7, 802.11ax chipset
- Coverage Range: 200m
- WAN & LAN – 10/100/1000/10000-BASE-T
- PoE 802.bt
- Power over DC2.0 54V/1A
- MLO (Multi-Link Operation) multi-frequency concurrency
- Automatic interference avoidance
- Up to 8 SSID (4 on 2.4GHz, 4 on 5.8GHz)
- Client Load Balancing
- AES Encryption
- VLANs
- PING Watchdog
- MAC Access control
- Easy to install
- Local or Cloud Management
- 1 Year warranty

Copyright © SilverNet Limited. All rights reserved. All other company and product names may be trademarks of their respective companies. Whilst every effort is made to make sure the information shown is accurate, SilverNet Limited can not accept liability for any errors that may arise. No freedom to use information, patents, trademarks or other intellectual property rights is implied by the publication of this document. E&OE. SilverNet Limited reserve the right to change specifications and other information within this document without notice and your attention is brought to the fact that performance figures are under ideal conditions. Actual performance will depend on many environmental factors, and it is recommended that a site survey is undertaken prior to installation. Please also note that this equipment may also be subject to local legislative restrictions. It is the end user's responsibility to ensure that the installation complies with any such restrictions that are in force.



Distributed By:

Superior Performance Features

5GHz Priority

Ensure you're always getting peak wireless networking performance.

The WCAP-7X automatically calculates the load balance and signal strength of 2.4GHz and 5.8GHz, allocating users to 5.8GHz first. This provides a high quality internet experience for your customers.

Seamless Roaming

Roaming has never been smoother.

802.11k and 802.11v Seamless Roaming provides smooth, unnoticeable switching to whichever access point has the most optimal signal when moving between APs.

Intelligent Spectrum Management

Success in the 2.4GHz and 5GHz spectrum requires an intelligent management system to remain interference free. The WCAP-7X has you covered.


It automatically selects the best channel on start-up, and uses an ongoing auto channel algorithm to alert and change channels if performance suffers due to interference.

Increased Efficiency with OFDMA

Reduced latency and efficient channel usage are the benefits of using OFDMA

Picture your Wi-Fi connection as a series of delivery vans, delivering data packets to your users. With 802.11ax, a "van" can deliver multiple packets to multiple users simultaneously, by splitting the bandwidth into individual "delivery" slots.

This results in a vast improvement in efficiency, working for both uploads and downloads.




802.11ax:

1024-QAM, Long OFDM Symbol, Max 160MHz bandwidth


802.11ac:

256-QAM

OFDM



OFDMA



Technical Specifications

Part No.	SIL WCAP-7X
Performance	
Max Throughput	2.4GHz 1148Mbps 5GHz 2882mbps 6GHz 5764Mbps
Client Capacity	384 users
Wireless Protocols	802.11ax/ac/a/n/g/b/be
Flash	SPI NOR 128MB
Memory	1024MB
Modes	WISP Wireless Range Extender (Repeater) Wired WiFi Extension (AP Mode)
Power Consumption	15W
Radio	
MIMO & Modulation	4x4 (2.4GHz) + 2x 2 (5GHz) + 2x2 (6GHz) MLO MIMO OFDMA Up to 4096-QAM
Bandwidth	20/40/80/160/320 MHz Channels
Frequency Range	2.4GHz - 2.484GHz 5.150GHz~5.850GHz 5.925GHz~7.125GHz
Max Output Power	20dBm
Antenna	
Type	Internal
Pattern	4dBi Omni
Interface	
LAN	10/100 /1000/2500M LAN Port,
WAN	10G WAN Port, support 802.3bt PoE input 10G WAN SFP+ Fiber Port
Reset Button	1x Reset Button (Press & Hold for 10 seconds to revert to factory default)
DC	DC2.0 54V/1A
Physical	
Dimensions (mm)	208mm x 208mm x 46mm
Enclosure	UV Stabilized Plastic
Weight	0.55kg
Environment	
Operating Temperature	-10°C to +40°C
Operating Humidity	5% to 95% Non-Condensing
Storage Temperature	-40°C to +70°C
Standards	
Approvals	IEC62368-1:2014+A11:2017, EN IEC 62311:2020, ETSI EN 301 489-1 ETSI EN 301 489-3, ETSI EN 301 489-17 ETSI EN 300 328, ETSI EN 300 440, ETSI EN 300 893
Safety	IEC/EN
RoHS Compliance	Yes
Wi-Fi Certified	Yes

Part Numbers & Accessories

802.11ax Access Points

Part Code	Description
SIL WCAP-EXT	Wi-Fi Standard 802.11ax/ac/n/a/g/b. Frequency 2.4GHz & 5GHz, Speeds up to 1800Mbps, Max TX Power 23Bm, 3dBi @ 2.4GHz; 6dBi @ 5.8GHz Integrated Omni Antenna, Up to 8 SSID Per Radio, Wireless Security WEP,WPA-PSK,WPA Enterprise, (WPA/WPA2,TKIP/AES) Concurrent clients 160+.
SIL WCAP-AX-EXT+	Wi-Fi Standard 802.11ax/ac/n/a/g/b. Frequency 2.4GHz & 5GHz, Speeds up to 1800Mbps, Max TX Power 24dBm, Quad N-Type Connector for Dual Band, Up to 8 SSID Per Radio, Wireless Security WEP,WPA-PSK,WPA Enterprise, (WPA/WPA2,TKIP/AES) Concurrent clients 160+.
SIL WCAP-AX-W	Wi-Fi standard 802.11ax/ac/n/a/g/b, Operating on 2.4GHz and 5GHz, at a speeds up to 1800Mbps, 2dBi 2.4GHz / 5dBi 5GHz Dual Band Omni with up to 8 SSID Per radio, range up to 50m with 120+ concurrent clients.

AP Controller

Part Code	Description
SIL WAC-AX	Dual-Core 1.8GHz CPU, 2GB DDR RAM, 32G SSD, Ethernet 5*10/100/1000Mbps LAN / WAN port, 1 x 10/100/1000Mbps WAN Port, 2x USB 1.1 Port, 1 x RJ45 Console Port, Power & SSID Indicator, Desk-top and Mount Rack.

